

Schüco AWS 75 VS



Even brighter rooms, even greater possibilities! Thanks to modern manufacturing and sustainability advances, aluminium has proven itself to be an excellent material for windows. Invest in the future and increase the value of your property with brand new aluminium window systems. Contact us today to help configure custom windows for your project.

Schüco - System solutions for windows, doors and façades

Based in Bielefeld, Schüco International KG develops and sells system solutions for windows, doors and façades. With more than 5.400 employees worldwide, the company strives to be the industry leader in terms of technology and service today and in the future. In addition to innovative products for residential and commercial buildings, the building envelope specialist offers consultation and digital solutions for all phases of a building project – from the initial idea through to design, fabrication and installation. 12,000 fabricators, developers, architects and investors around the world work together with Schüco. The company is active in more than 80 countries and achieved a turnover of 2,11 billion Euros in 2023. For more information, visit www.schueco.com

SCHÜCO



Schüco AWS 75 VS

A brandnew elegant window system



Schüco AWS 75 VS

A brand-new Schüco window system designed for your needs



Schüco AWS 75 VS

With Schüco AWS 75 VS (Vertical Slider) the demand for aluminum hung window is fulfilled by combining Schüco brand reliability and experience. Thanks to its elegant and modern design, it can be preferred in both new construction projects and renovation works.

In addition to vertical sliding opening, it also offers tilt opening function, providing users with easy cleaning and maintenance.

Schüco AWS 75 VS is the ideal product for projects with its reliability and versatility. This solution is the hung window system among the current Schüco window series. Considering building physics requirements, customers comfort and Project budget, a perfect solution has been offered in every aspect.

Product Benefits and Features	
▪75 mm basic depth ▪Glass thickness of 22 mm to 42 mm for fixed light and operable units ▪Wide colour range ▪Expanding market area with a new product solution ▪Providing Schüco quality and brand reliability into the vertical sliding market ▪Adequate thermal insulation thanks to double insulation zone ▪Additional tilt function for maintenance ▪Quite and easy operation ▪Onsite assembly possibility of outer frame with screwed butt joint, an advantage in transportation	

Technical Data		
Max. Vent Weight	45 kg	
Max. Window Width	1.030 mm*	
Max. Window Height	2.200 mm*	
Min. Window Width	610 mm	
Min. Window Height	944 mm	
Test	Standard	Value
Wind Load Resistance	DIN EN 12210 ASTM E330	2400 Pa (±50 psf)
Air Permeability	DIN EN 12207 ASTM E283	300 Pa (6,25 psf)
Watertightness	DIN EN 12208 ASTM E331	360 Pa (7,5 psf)
U _f Value	DIN EN ISO 10077-2	3,1 to 3,8 W/m²K